


Port Powered, Asynchronous, Fiber Optic Modems CE Models 1110F, 1110M

Description:

The Model 1110 series miniature fiber optic modems support data rates up to 19.2 Kbps and distances to up 3.2 kilometers (2 miles). The Model 1110 operates full or half duplex and plugs directly into a workstation's RS-232 port.

Like all fiber optic modems, the Model 1110 is inherently immune to RFI/EMI noise, ground loops and transient surges.



Features:

- Communicates over dual optical fibers
- Data rates to 19.2 Kbps
- Range to 3.2 Km (2 miles)
- Two easy-to-read status indicators
- No AC power required
- External DCE/DTE switch
- Male or female DB-25 and ST fiber optic connectors

Specifications:

Size:	6.8 x 5.3 x 1.9 cm (2.66" x 2.10" x 0.73")
Weight:	62 grams (2 oz.)
Interfaces:	EIA RS-232. CCITT V.24
RTS/CTS Delay:	Switch-selectable: No delay, 9.5mS, 79.5 mS
Receiver Sensitivity:	-45 dBm
Coupled Power Output:	-30 to -36 dBm
Optic Wavelength:	850 nm
LED indicators:	Carrier Detect and Fiber Optic Output
Temperature Range:	0-60 deg.C (32-140 deg.F)



1996 B&B Electronics -- Revised April 1999

B&B Electronics Mfg. Co.
 707 Dayton Road - P.O. Box 1040 - Ottawa, IL 61350 USA
 Phone: (815) 433-5100 - Fax: (815) 434-5105
 Home Page: www.bb-elec.com
 Sales e-mail: sales@bb-elec.com - Fax: (815) 433-5109
 Technical Support e-mail: support@bb-elec.com - Fax: (815) 433-5104

B&B Electronics Ltd
 Westlink Commercial Park - Oranmore, Co. Galway - Ireland
 Phone: (353) 91 792444 - Fax: (353) 91 792445
 Home Page: www.bb-europe.com
 Sales e-mail: sales@bb-europe.com
 Technical Support e-mail: support@bb-europe.com