



GSC FUSE

Electronic / Glass Fuses

Time Delay—5mm x 20mm

Description

- Standard
- Glass Body
- Time Delay
- 5mm x 20mm
- 1/10A through 3A, 250VAC - UL Listed and CSA Certified
- 4A through 8A, 125VAC - UL Listed and CSA Certified
- 10A and 15A, 250VAC - UL Recognized

Highlights

- Time Delay

Standard Fuse Ampere Ratings

CATALOG NUMBER	AMPERE RATING	VOLTS	I.R. (see notes) *
GSC1/10	1/10A	250V	1
GSC1/8	1/8A	250V	1
GSC1/4	1/4A	250V	2
GSC3/10	3/10A	250V	2
GSC4/10	4/10A	250V	2
GSC1/2	1/2A	250V	2
GSC6/10	6/10A	250V	2
GSC7/10	7/10A	250V	2
GSC3/4	3/4A	250V	2
GSC8/10	8/10A	250V	2
GSC1	1A	250V	2
GSC1-1/4	1-1/4A	250V	1
GSC1-1/2	1-1/2A	250V	1
GSC1-6/10	1-6/10A	250V	1
GSC2	2A	250V	1
GSC2-1/2	2-1/2A	250V	1
GSC3	3A	250V	1
GSC4	4A	125V	3
GSC5	5A	125V	3
GSC6	6A	125V	3
GSC7	7A	125V	3
GSC8	8A	125V	3

*

1: 250VAC @ 100A I.R./125VAC @ 10kA I.R.

2: 250VAC @ 35A I.R./125VAC @ 10kA I.R.

3: 1 125VAC @ 10kA I.R.