

EAT•N

Powerware

Powerware® Multi-Server Card

Product Focus



Managers need products that give them maximum control of their power environment and protect their systems from the harmful effects of power irregularities. The Powerware Multi-Server Card fills a critical market need, allowing users to monitor their power environment and gracefully shut down multiple protected computer systems with a mixture of various operating systems.

This product is designed to function with any Powerware UPS that has an X-Slot com-

UNITED STATES
8609 Six Forks Road
Raleigh, NC 27615 U.S.A.
Toll Free: 1.800.356.5794
or 919.872.3020

www.powerware.com

Features

- Multiple serial ports provide greater power management control and flexible monitoring
- LanSafe™ software compatibility provides simultaneous monitoring of computer loads supporting various operating systems
- Independent control of serial ports gives load shedding capability for maximum runtime of critical loads
- Simultaneously provides RS-232 monitoring and relay output monitoring
- Plug and Play (PnP) protocol for easy configuration
- The Multi-Server Card works with: Powerware 9340; Powerware 9330; Powerware 9125; Powerware 5125; Expansion Chassis

munication device, and is also compatible with Powerware Expansion Chassis. The Multi-Server Card has six serial ports, three of which correspond with the multiple load segments of your Powerware UPS. By utilizing multiple serial cables and LanSafe software, you can perform simultaneous yet independent monitoring and control of up to six servers with a mixture of operating systems.

This feature allows a manager to configure each server to provide a graceful shutdown at the

optimum time desired, allowing the most critical loads the maximum runtime available.

The Multi-Server Card includes one serial port that provides monitoring for low battery, on bypass, or utility failure conditions. This port also is used for configuration of the Multi-Server Card. Plug and Play (PnP) protocol allows easy configuration by automatically identifying the type of PnP device attached to the serial ports.

CANADA
Ontario: 416.798.0112

LATIN AMERICA
Argentina: 54.11.4343.6323
Brazil: 55.11.3616.8500
México: 52.55.5488.5252

EUROPE/MIDDLE EAST/AFRICA
Denmark: 45.3686.7910
Finland: 358.94.52.661
France: 33.1.6012.7400
Germany: 49.7841.666.0
Italy: 39.02.66.04.05.40
Norway: 47.23.03.65.50
Sweden: 46.8.598.940.00
United Kingdom: 44.1753.608.700

TECHNICAL SPECIFICATIONS

Part number	05146447-5502
Description	X-Slot™ card with multiple serial connections for serial communications with Powerware UPSs
UPS compatibility	PW 5125, PW 9125, PW 9155, PW 9315, PW 9330, PW 9340, PW 9390, Expansion Chassis
Serial cable	PN 124102022-002
O/S supported for shutdown	All O/S supported by Powerware LanSafe Operating temperature 0 to 40°C
Operating humidity	10-80% non-condensing
Power input	9VDC unregulated
Power consumption	1.5 Walls
Dimensions LxWxH (in)	4.7x4.5x1.5
(mm)	120x114x39
Weight	7 oz.
Regulatory	FCC Class An

ASIA PACIFIC
Australia/NZ: 61.2.9878.5000
China: 86.21.6361.5599
HK/Korea/Taiwan: 852.2745.6682
India: 91.11.2649.9414 to 18
Singapore/SEA: 65.6829.8888

Powerware and ABM are trade names, trademarks and/or service marks of Eaton Power Quality Corporation or its subsidiaries and affiliates. All other trademarks are property of their respective owners.

© 2005 Eaton Corporation
All Rights Reserved
Printed in USA
SFT28FXA
June 2005

EAT•N

Powerware